


汚水樹 SC型

記号	組合せ	H	h	重量(kg)
SC-1	6A+6B	850	576~ 744	232
SC-2	6A+6B+6C	950	676~ 844	256
SC-3	6A+6B+6D	1050	776~ 944	280
SC-4	6A+6B+6C+6D	1150	876~1044	304
SC-5	6A+6B+6E	1250	976~1144	328
SC-6	6A+6B+6C+6E	1350	1076~1244	352

雨水樹 RC型

記号	組合せ	H	h	重量(kg)
RC-1	6A+6B	850	456~ 624	232
RC-2	6A+6B+6C	950	556~ 724	256
RC-3	6A+6B+6D	1050	656~ 824	280
RC-4	6A+6B+6C+6D	1150	756~ 924	304
RC-5	6A+6B+6E	1250	856~1024	328
RC-6	6A+6B+6C+6E	1350	956~1124	352
RC-7	6A+6B+6D+6E	1450	1056~1224	376



ます蓋 (7-割)	寸法			縦筋		横筋		寸法の許容差			重量(kg)
	a	b	h	径(mm)	本数	径(mm)	本数	a	b	h	
600用(汚・雨)	720	710	58	4.0	8	4.0	8	±2	±2	±2	51

記号	呼び名	配筋				寸法の許容差					重量(kg)
		縦筋 径(mm)	本数	巻筋 径(mm)	本数	ますの内径	厚さ	高さ	管取付部	ふた受部	
6A	600X200	3.5	8	3.5	5	±4	+4-2	+2	—	±2	84
6B	600X650	3.5	8	3.5	7	±4	+4-2	+2	±2	—	148
6C	600X100	3.5	8	3.5	3	±4	+4-2	+2	—	—	24
6D	600X200	3.5	8	3.5	3	±4	+4-2	+2	—	—	48
6E	600X400	3.5	8	3.5	4	±4	+4-2	+2	—	—	96

品名 図番 製 図	600m/m用円型樹 (遠心力工法)			
	M059161A		縮尺	日付
	検	承	認	
絨永CMC株式会社				